


# Beckry® Pol



Black



Brite White



Quaker Gray



Pewter Gray



Clay



Sandstone




Crimson




Pebble Beige



Burnished Slate



Earth Brown



Barn Red



Rawhide Tan



Slate Blue



Royal Blue



Evergreen



Burgundy

**Note:** The colors on this card are produced as closely as possible to the Beckry® Pol paint colors and are for guidance only. Actual color panels are available upon request. For more information on additional colors or custom colors, please contact the sales team at [info-beckersspecialty@beckers-group.com](mailto:info-beckersspecialty@beckers-group.com).

## Product Specifications

- Pencil Hardness (ASTM D 3363<sup>1</sup>): F-H, Eagle Turquoise
- Gloss @ 60° (ASTM D 523): 15 to 80+
- Solvent Resistance (ASTM D5402): 50+ MEK double rubs
- Reverse Impact Resistance (ASTM D 2794<sup>2</sup>): 1.5 x metal thickness / no pick-off
- Flexibility / T-Bend (ASTM D 4145<sup>2</sup>): 1T no pick-off
- Metal Marking Resistance: Excellent
- Eligible for warranty. Please contact your Sales Representative for details.

All product specifications are based on a flat panel with proper pretreatment. Testing has been conducted on two coat HDG Steel / Galvalume® / Aluminum.  
1 - American Society for Testing and Materials.  
2 - Beckery® Tech was not designed to bridge breaks in the substrate.

## Substrates

- Galvalume®
- Galvanized Steel
- Aluminum

## Benefits

- Unique Appearances Available
- Outperforms Traditional SMP's
- Flexibility
- Color Consistency

## Suggested Applications

- Carports
- Architectural Projects
- Metal Building / Roofing Panels